## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources								
Supplier's name or trade mark: SOLAR STINGER								
Supplier's address: ECONLUX GmbH, Industriestrasse 154, 50996 Köln, DE								
Model identifier: SunStrip 70 Fresh 650								
Type of light source:								
Lighting technol	logy used:	LED	Non-directional or directional:	DLS				
Light source cap-type (or other electric interface)		6-Pin Plug						
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein				
Colour-tuneable light source:		Nein	Envelope:	-				
	High luminance light source:							
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers				
Product parameters								
Parameter		Value	Parameter	Value				
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		46	Energy efficiency class	G				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 803 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	8 600				
On-mode power (P <sub>on</sub> ), expressed in W		46,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	91				
Outer dimensions	Height	24	Spectral power	See image				
	Width	650	distribution in the	in last page				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	90	range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,289 0,302			
Parameters for directional light sources:							
Peak luminous intensity (cd)		986	Beam angle in degrees, or the range of beam angles that can be set	110			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		60	Survival factor	-			
the lumen maintenance factor		-					

(a)'-': not applicable; (b)'-': not applicable;

